

UltraTac™ is a 0.5 mil (12µ) clear PET high tack, high bond strength film, coated on both sides with a pressure sensitive acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with siliconized PE. The adhesive is self-wound on the release liner.

### PRODUCT STRUCTURE

<b>Adhesive</b>	Acrylic (Pressure Sensitive)
<b>Film</b>	Clear PET
<b>Adhesive</b>	Acrylic (Pressure Sensitive)
<b>Release Liner</b>	2 Side PE Coated, 2 Side Siliconized Kraft

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	0.5 mil (12µ)
<b>Adhesive Layer</b>	1.1 mil (28µ) on each side
<b>Film/Adhesive Ratio</b>	1.1:0.5:1.1
<b>UV Protection Factor</b>	Not Applicable
<b>Outdoor Durability</b>	Not Applicable
<b>Service Temperature Range</b>	-4°F to 248°F (-20°C to 120°C)
<b>Shelf Life</b>	1 year
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

### PROCESS SETTINGS

Equipment Type & Temperature	Speed
<b>Roller Laminator</b> Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
<b>Press</b>	Not recommended

**DRYTAC®**  
ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
bristol@drytac.com  
Tel: +44 (0) 117 958 6500

#### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
toronto@drytac.com  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
customerservice@drytac.com  
Tel: +1 800.280.6013

- ULTRATAC™ IS A HIGH GRADE VERSION OF MEDIATAC™, SUITABLE FOR ALL THE SAME APPLICATIONS AND DESIGNED FOR MOUNTING GRAPHICS ONTO MORE DIFFICULT SUBSTRATES, SUCH AS FOREX™, MDF, GATORBOARD™, ULTRABOARD™, FOAMEX™, OR SINTRA™.

For more information,  
performance and warranty guide  
lines please contact your local  
Drytac office.

© 2018 Drytac Corporation. E&OE.  
All other trademarks are the property  
of their respective owners.