

ArmourPrint™ Emerytex® & ArmourGrab™

Counter Mat Solution

Drytac® ArmourPrint™ Emerytex® and ArmourGrab™ work together perfectly to create a counter mat solution ideal for fast food and retail environments. ArmourPrint™ Emerytex® is a clear, 15 mil (381µ) heavy-duty, slip resistant monomeric PVC film with a matte pebble textured finish on one side and a smooth printable surface on the other side. By reverse-printing onto ArmourPrint™ Emerytex® and pairing it with ArmourGrab™ – a 8 mil (203µ) co-extruded white film coated with a heavy coat weight, permanent, pressure sensitive clear acrylic adhesive – you can create eye-catching advertising mats for counters. ArmourPrint™ Emerytex® has been approved by the FDA for incidental food contact and both media are slip-resistant, making the combination safe and effective for counters in fast food outlets, convenience stores, bars and more.

- NON-SLIP FOR CONVENIENCE ON COUNTERS
- CERTIFIED FOR INCIDENTAL FOOD CONTACT
- UV PROTECTION FOR USE OUTDOORS
- MOISTURE BARRIER FOR HYGIENE AND PROTECTION

Product Code: ARP & ARG

23
mil
total solution

☐ Matte
Pebble Finish

☐ Adhesive Coated
Anti-Slip White



ArmourPrint™ Emerytex®
(Eco)Solvent
Latex
UV



ArmourPrint™ Emerytex®
No Adhesive

ArmourGrab™
High Coat Weight Clear
Permanent Acrylic



Widths up to 54in



EXTERIOR & INTERIOR

NON-SLIP/FOOD-SAFE COUNTER-TOP ADVERTISING



APPLICATIONS

COUNTER-TOP ADVERTISING

PLACEMATS

MOUSE PADS



DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

ArmourPrint™ Emerytex®

Counter Mat
Solution Component

Drytac's ArmourPrint™ Emerytex® is a clear heavy duty, slip resistant monomeric PVC film with a matte pebble textured finish on one side and a smooth printable surface on the other side. ArmourPrint™ Emerytex® has been tested according to the EN 13036-4 test method and awarded a rating of low slip potential. The film is compliant with Registration, Evaluation, Authorization and Restriction of Chemical Substances (REACH) and California Prop 65.

- PROVIDES UV PROTECTION FOR OUTDOOR GRAPHICS
- IDEAL FOR TRADESHOW GRAPHICS, POP DISPLAYS, MOUSE PADS, COUNTER MATS, EVENT SIGNAGE AND OTHER SIGNAGE WHERE A SCUFF RESISTANT FINISH IS REQUIRED

Paired Product

Recommendation:

ArmourPrint™ Emerytex® can be adhered with Drytac's ArmourGrab™ which is used as a non-skid product.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film

One Side: Matte Pebble Textured Finish
One Side: Smooth Printable Surface

PRODUCT CHARACTERISTIC

Film Thickness

15 mil (381µ)

Outdoor Durability

2 Years

Slip Rating

Low Slip Potential
(According to EN 13036-4)

FDA Rating

Indirect Food Contact
US FDA 21 CFR 175.300
US FDA 21 CFR 177.1975

Shelf Life

1 year

Storage Conditions

59°F to 72°F (15°C to 22°C);
50 - 55% Relative Humidity

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com

Counter Mat Solution Component

ArmourGrab™ is a 8 mil (203μ) co-extruded white film coated with a heavy coat weight, permanent, pressure sensitive clear acrylic adhesive. The product has an anti-slip surface on the back face, which makes it ideal for the construction of counter mats, mousepads and placemats.

- IDEAL BACKING MATERIAL FOR ANY APPLICATION WHICH REQUIRES A NON-SKID SURFACE
- MOISTURE BARRIER FOR CONSTRUCTION APPLICATION

Paired Product

Recommendation:

When using ArmourGrab™, use Drytac's ArmourPrint™ Emerytex® for printing on to its smooth surface. Emerytex has a matte pebble finish on the back side. For more information, please refer to the Drytac ArmourPrint™ Emerytex® TDS.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Adhesive Coated Anti-Slip White
Adhesive	High Coat Weight Clear Permanent Acrylic (Pressure Sensitive)
Release Liner	63# Poly Coated Kraft

PRODUCT CHARACTERISTIC

Film Thickness	8 mil (203μ)	9.2mil
Adhesive Layer	1.2 mil (30μ)	(233μ)
Film/Adhesive Ratio	8:1.2	
Peel Strength (24 Hour Test)	68 ozf/in (1mil on Stainless steel at 180°)	
Application Temperature	>41°F (5°C)	
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)	
Shelf Life	1 year	
Storage Conditions	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity	

DRYTAC
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

105 Nuggett Court,
Brampton,
Ontario, L6T 5A9,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013