

Polar®

Chrome

Polar® Chrome is a 2 mil (50µ) printable satin silver PET film with a clear permanent acrylic adhesive. Its reflective satin finish brings a sleek, modern look to graphics, making it ideal for high-impact indoor outdoor use. Perfect for signage, billboards, POS displays, transit advertising, and exhibitions, Polar® Chrome ensures your message shines with clarity and style.

As a PVC-free solution, Polar® Chrome supports more environmentally conscious graphics production without compromising on performance or visual appeal. Its polyester base offers excellent dimensional stability, making it a smart choice for brands and print providers looking to reduce their environmental footprint.

PRODUCT CODE: PCH

2.0
mil

Silver
Reflective
PET



Satin



(Eco) Solvent
Latex/Resin
UV



Clear
Permanent
Adhesive



Widths up to 54 in



INTERIOR



EXTERIOR

ULTRA REMOVABLE, PVC-FREE GRAPHICS



APPLICATIONS

SIGNAGE

BILLBOARDS

EXHIBITION HALLS

RETAIL & POP DISPLAY



www.drytac.com

Polar®

Chrome

Polar® Chrome is a 2 mil (50µ) premium, silver satin PET film with a clear permanent acrylic adhesive that is protected by a 90# 2 side PE coated, 1 side siliconized white kraft release liner. This bold reflective media serves as an excellent PVC-free choice to create engaging displays and signage.

The film's versatility allows it to be used with a wide range of printers including (Eco) Solvent, Latex/Resin, and UV.

Polar® Chrome provides a superb printing surface for eye-catching color graphics, interior or exterior.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2025 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATIONS

PRODUCT STRUCTURE

Film	Silver Satin PET
Adhesive	Clear Permanent Acrylic (Pressure Sensitive)
Release Liner	90# 2 Side PE Coated, 1 Side Siliconized White Kraft

PRODUCT CHARACTERISTICS

Film Thickness	2 mil (50µ)
Adhesive Layer	1 mil (25µ)
Outdoor Durability	2 Years (Ink Dependent)
Application Temperature	>-5°F (-20°C)
Service Temperature Range	-49°F to 230°F (-45°C to 110°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity



Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com