Polar®

Chome

Polar® Chrome is a 2 mil (50µ) printable satin silver PET film with a clear permanent acrylic adhesive. Its reflective satin finish brings a sleek, modern look to graphics, making it ideal for high-impact indoor outdoor use. Perfect for signage, billboards, POS displays, transit advertising, and exhibitions, Polar® Chrome ensures your message shines with clarity and style.

As a PVC-free solution, Polar® Chrome supports more environmentally conscious graphics production without compromising on performance or visual appeal. Its polyester base offers excellent dimensional stability, making it a smart choice for brands and print providers looking to reduce their environmental footprint.

2.0 Silver Reflective PET







Clear Permanent Adhesive

mimimimim

Widths up to 54 in







APPLICATIONS

SIGNAGE
BILLBOARDS
EXHIBITION HALLS
RETAIL & POP DISPLAY



Polar

Chrome

TECHNICAL SPECIFICATIONS

Polar® Chrome is a 2 mil (50μ) premium, silver satin PET film with a clear permanent acrylic adhesive that is protected by a 90# 2 side PE coated, 1 side siliconized white kraft release liner. This bold reflective media serves as an excellent PVC-free choice to create engaging displays and signage.

Polar® Chrome provides a superb printing surface for eye-catching color graphics, interior or exterior. Its metallic finish enhances printed colors with a striking depth and vibrancy, making it ideal for high-impact retail displays, window graphics, and promotional signage. Durable and easy to work with, Polar® Chrome delivers long-lasting results that combine visual appeal with environmental responsibility

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2025 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

PRODUCT STRUCTURE

Film	Silver Satin PET
Adhesive	Clear Permanent Acrylic (Pressure Sensitive)
Release Liner	90# 2 Side PE Coated, 1 Side Siliconized White Kraft

PRODUCT CHARACTERISTICS

Film Thickness	2 mil (50µ)
Adhesive Layer	1 mil (25µ)
Outdoor Durability	2 Years (Ink Dependent)
Application Temperature	>-5°F (-20°C)
Service Temperature Range	-49°F to 230°F (-45°C to 110°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity



Europe

Filwood Road, Fishponds, Bristol, BS16 3RY, United Kingdom bristol@drytac.com

Tel: +44 (0) 117 958 6500

Canada

30 Driver Road, Brampton, Ontario, L6T 5V2, Canada toronto@drytac.com Tel: +1 800.353.2883

USA

5401-B Eubank Road, Sandston, Virginia, 23150, USA customerservice@drytac.com

Tel: +1 800.280.6013