Polar

Chome

Polar® Chrome is a 2 mil (50µ) printable satin silver PET film with a clear permanent acrylic adhesive. Its reflective satin finish brings a sleek, modern look to graphics, making it ideal for high-impact indoor outdoor use. Perfect for signage, billboards, POS displays, transit advertising, and exhibitions, Polar® Chrome ensures your message shines with clarity and style.

As a PVC-free solution, Polar® Chrome supports more environmentally conscious graphics production without compromising on performance or visual appeal. Its polyester base offers excellent dimensional stability, making it a smart choice for brands and print providers looking to reduce their environmental footprint.

50 micron

Silver Reflective PFT





Latex/Resin UV



Clear Permanent Adhesive

mimimimimim

Widths up to 1370 mm





STUNNING, EYE-CATCHING SILVER SATIN GRAPHICS



SIGNAGE
BILLBOARDS
EXHIBITION HALLS
RETAIL & POP DISPLAY



Polare

Chrome

TECHNICAL SPECIFICATION

Polar® Chrome is a 2 mil (50μ) premium, silver satin PET film with a clear permanent acrylic adhesive that is protected by a 90# 2 side PE coated, 1 side siliconized white kraft release liner. This bold reflective media serves as an excellent PVC-free choice to create engaging displays and signage.

Polar® Chrome provides a superb printing surface for eye-catching color graphics, interior or exterior. Its metallic finish enhances printed colors with a striking depth and vibrancy, making it ideal for high-impact retail displays, window graphics, and promotional signage. Durable and easy to work with, Polar® Chrome delivers long-lasting results that combine visual appeal with environmental responsibility

PRODUCT STRUCTURE

Release Liner	90# 2 Side PE Coated, 1 Side Siliconized White Kraft
Adhesive	Clear Permanent Acrylic (Pressure Sensitive)
Film	Silver Satin PET

PRODUCT CHARACTERISTICS

Film Thickness	2 mil (50µ)
Adhesive Layer	1 mil (25µ)
Outdoor Durability	2 Years (Ink Dependent)
Application Temperature	>-5°F (-20°C)
Service Temperature Range	-49°F to 230°F (-45°C to 110°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2025 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.



Europe

Filwood Road, Fishponds, Bristol, BS16 3RY, United Kingdom bristol@drytac.com Tel: +44 (0) 117 958 6500

Canada

30 Driver Road, Brampton, Ontario, L6T 5V2, Canada toronto@drytac.com Tel: +1 800.353.2883

USA

5401-B Eubank Road, Sandston, Virginia, 23150, USA customerservice@drytac.com Tel: +1 800.280.6013