

Polar®

Premium Air PB

Polar® Premium Air has a unique adhesive with bubble-free technology which makes for an easy install. The high opacity of Polar® Premium Air provides an excellent printing surface and offers a consistent white point. This phthalate-free film also offers excellent indoor and outdoor durability. Polar® Premium Air maximizes adhesive performance on a wide variety of substrates.

- POLAR PREMIUM AIR IS AVAILABLE WITH A PERMANENT ADHESIVE
- BUBBLE-FREE AIR EGRESS TECHNOLOGY FOR EASY INSTALLATION
- IDEAL FOR INDOOR & OUTDOOR GENERAL SIGNAGE & DISPLAY
- CAN BE USED FOR VEHICLE SURFACES- FLAT OR SLIGHTLY CURVED SURFACES

3.2
mil

White
Polymeric
PVC

Matte or
Gloss



(Eco) Solvent
Latex
UV



Grey Permanent
Adhesive with
Bubble-Free
Technology



Widths up to 60 in



INTERIOR & EXTERIOR
(with matched overlamine)

EASY TO APPLY, EXCELLENT PRINTING SURFACE



APPLICATIONS

GENERAL SIGNAGE
EXHIBITION GRAPHICS
POS DISPLAY
TRANSIT ADVERTISING
ARENA ADVERTISING



DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

Premium Air PB

Polar® Premium Air is a 3.2 mil (80µ) premium, phthalate-free printable polymeric self-adhesive PVC film with a high quality, acrylic adhesive. Polar® Premium Air has a permanent adhesive with bubble-free technology which makes for an easy install. The high opacity of Polar® Premium Air provides a consistent printing surface and offers a superb white point. Polar® Premium Air has either a gloss or matte finish with a permanent adhesive for optimum adhesive performance on a wide variety of substrates.

- POLAR PREMIUM AIR WHITE GLOSS PB (PAGP) White Gloss Film with a Permanent Grey Adhesive
- POLAR PREMIUM AIR WHITE MATTE PB (PAMP) White Matte Film with a Permanent Grey Adhesive

INSTALLATION

RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2022 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

11232022

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte or Gloss White Polymeric PVC
Adhesive	Grey Permanent Acrylic (Pressure Sensitive)
Release Liner	90# PE Coated Kraft with Air Egress

PRODUCT CHARACTERISTICS

Film Thickness	3.2 mil (80µ) 4.2 mil
Adhesive Layer	1 mil (25µ) (105µ)
Outdoor Durability	5 Years; Ink Dependent
Fire Ratings	Class A or Class 1 (ASTM E-84) PASS (CAN/ULC-S102)
Application Temperature	-5°F (-20°C)
Service Temperature Range	-49°F to 230°F (-45°C to 110°C)
Shelf Life	2 Years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

OVERLAMINATE RECOMMENDATIONS

When using Polar® Premium, an overlaminate can be used for maximum life expectancy. Products recommended for use with Polar® Premium are Drytac's WipeErase® Clear, and Interlam™ Pro overlaminates.

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013