

# SpotOn®



## White M50

Perfect for window graphics and for short-term indoor applications such as wall, tradeshow or retail graphics that require seasonal change out. SpotOn® White M50 is 50% more opaque than standard SpotOn® White products. This high quality, ink receptive printable vinyl has a unique dot pattern removable adhesive that is virtually undetectable, but allows graphics to be installed with minimal effort, remain in place for the duration of the application, and removed with ease. The film's adhesive allows for easy, bubble-free application of vibrant graphics to a wide range of substrates without the need for tools or wet installation.

- PROP 65 COMPLIANT
- EASY TOOL & BUBBLE FREE APPLICATION
- CAN BE REMOVED EASILY WITHIN 12 MONTHS

Product Code: SPOE

**100** Micron Matte Monomeric PVC  Matte



EASY BUBBLE FREE APPLICATION

**50% OFF**

[www.drytac.com](http://www.drytac.com)

### APPLICATIONS

Indoor Signage  
Retail Promotions  
Window Graphics  
Wall Graphics



**DRYTAC®**  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

# SpotOn®

## White M50

SpotOn® White M50 is a 4 mil (100µ) printable white matte monomeric PVC film with a dot-patterned, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single-sided, siliconized clay coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy, bubble-free application of vibrant graphics to a wide range of substrates. The light block properties of SpotOn® White M50 make it up to 50% more opaque than the standard SpotOn® White product.

- IDEAL FOR SHORT-TERM INDOOR WALL AND WINDOW APPLICATIONS
- INCREASED OPAQUENESS PREVENTS SHOW THROUGH FROM THE SUBSTRATE
- CAN BE REMOVED EASILY WITHIN 12 MONTHS

### INSTALLATION

#### RECOMMENDATION

Please see SpotOn® installation instructions for further details. The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2018 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	White Matte Monomeric PVC
<b>Adhesive</b>	Dot Pattern Removable Polyacrylate
<b>Release Liner</b>	140 gsm 1 Side Siliconised PE Coated Kraft

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	4 mil (100µ)	4.5 mil (113µ)
<b>Adhesive Layer</b>	0.5 mil (13µ)	
<b>Outdoor Durability</b>	6 months	
<b>Application Temperature</b>	>41°F (5°C)	
<b>Service Temperature Range</b>	-4°F to 149°F (-20°C to 65°C)	
<b>Fire Rating</b>	B1 (DIN 4102-1) PASS (CAN/ULC-S102) Class B (EN 13501-1)	
<b>Shelf Life</b>	1 year	
<b>Storage Conditions</b>	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity	

# DRYTAC®

## ADHESIVE SCIENCE

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013

[www.drytac.com](http://www.drytac.com)