

# SpotOn®

## SynTac™

SpotOn® SynTac™ is a 3.7 mil (92 $\mu$ ) white matte or clear gloss polypropylene (PP) film designed for effortless, tool-free installation. Its innovative dot-patterned, removable polyacrylate adhesive allows for bubble-free application on a wide range of surfaces, and it can be cleanly removed within 12 months.

Developed with sustainability in mind, SpotOn SynTac is perfect for seasonal promotions, short-term campaigns, or peel-and-stick signage where easy removal is key.

### Product Codes:

**SPOS** - SpotOn SynTac White Matte

**SPOX** - SpotOn SynTac Clear Gloss

**3.7**  
mil

White Matte or  
Clear Gloss  
Polypropylene (PP)



Latex\*/Resin  
UV



Removable  
Dot Pattern Polyacrylate  
Adhesive



Widths up to 54 in



INTERIOR



EXTERIOR

**EASY TO APPLY AND ECO-FRIENDLY**



### APPLICATIONS

WINDOW GRAPHICS

WALL GRAPHICS

RETAIL SPACES

EVENT SIGNAGE



**DRYTAC®**  
**ZERO**

[www.drytac.com](http://www.drytac.com)

# SpotOn®

## SynTac™

SpotOn® SynTac™ is a 3.7 mil (92 $\mu$ ) printable matte white or gloss clear polypropylene film featuring a removable, dot-pattern pressure-sensitive polyacrylate adhesive. Protected by a single-sided, siliconized hybrid PE-coated release liner, this eco-conscious, ink-receptive synthetic film is ideal for indoor and short-term outdoor applications where easy installation and clean removal are essential.

### ● TOOL-FREE, BUBBLE-FREE APPLICATION

Thanks to its dot-pattern adhesive, SpotOn SynTac installs effortlessly without the need for tools or professional installers.

### ● ECO-CONSCIOUS AND PVC-FREE

Made from polypropylene, this film offers a sustainable alternative to traditional PVC graphics media—ideal for environmentally focused projects.

### ● VERSATILE & REMOVABLE

Perfect for both indoor and short-term outdoor applications, SpotOn SynTac removes cleanly within 12 months, leaving no residue behind.

\*Latex Ink Compatibility Note: For optimal results, use with HP Latex 4th generation ink technology.

**For more information,  
performance and warranty  
guidelines please contact your  
local Drytac office.**

© 2026 Drytac Corporation. E&OE.  
All other trademarks are the property  
of their respective owners.

## TECHNICAL SPECIFICATIONS

### PRODUCT STRUCTURE

#### Film

White Matte Polypropylene (PP) or Clear Gloss Polypropylene (PP)

#### Adhesive

Clear Removable Dot Pattern Polyacrylate

#### Release Liner

Hybrid PE liner

### PRODUCT CHARACTERISTICS

#### Film Thickness

3.7 mil (92 $\mu$ )

#### Adhesive Layer

1.1 mil (28 $\mu$ )

#### Outdoor Durability

6 Months

#### Fire Rating

B-s1,d0 (EN13501-1)

#### Application Temperature

>41°F (5°C)

#### Service Temperature Range

-4°F to 203°F  
(-20°C to 95°C)

#### Shelf Life

2 Years

#### Storage Conditions

64°F to 77°F (18°C to 25°C);  
40 - 65% Relative Humidity



#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013