

# SpotOn®

## SynTac™

### EASY TO APPLY AND ECO-FRIENDLY

SpotOn® SynTac™ is a 3.7 mil (92µ) white matte or clear gloss polypropylene (PP) film designed for effortless, tool-free installation. Its innovative dot-patterned, removable polyacrylate adhesive allows for bubble-free application on a wide range of surfaces, and it can be cleanly removed within 12 months.

Developed with sustainability in mind, SpotOn SynTac is perfect for seasonal promotions, short-term campaigns, or peel-and-stick signage where easy removal is key.

#### Product Codes:

**SPOS** - SpotOn SynTac White Matte

**SPOX** - SpotOn SynTac Clear Gloss

**92** White Matte or  
micron Clear Gloss  
Polypropylene (PP)



Latex\*/Resin  
UV



Removable  
Dot Pattern Polyacrylate  
Adhesive



Width 1370mm



INTERIOR



EXTERIOR



#### APPLICATIONS

WINDOW GRAPHICS

WALL GRAPHICS

RETAIL SPACES

EVENT SIGNAGE



[www.drytac.com](http://www.drytac.com)

# SpotOn®

## SynTac™

SpotOn® SynTac™ is a 3.7 mil (92µ) printable matte white or gloss clear polypropylene film featuring a removable, dot-pattern pressure-sensitive polyacrylate adhesive. Protected by a single-sided, siliconized hybrid PE-coated release liner, this eco-conscious, ink-receptive synthetic film is ideal for indoor and short-term outdoor applications where easy installation and clean removal are essential.

- **TOOL-FREE, BUBBLE-FREE APPLICATION**

Thanks to its dot-pattern adhesive, SpotOn SynTac installs effortlessly without the need for tools or professional installers.

- **ECO-CONSCIOUS AND PVC-FREE**

Made from polypropylene, this film offers a sustainable alternative to traditional PVC graphics media—ideal for environmentally focused projects.

- **VERSATILE & REMOVABLE**

Perfect for both indoor and short-term outdoor applications, SpotOn SynTac removes cleanly within 12 months, leaving no residue behind.

\*Latex Ink Compatibility Note: For optimal results, use with HP Latex 4th generation ink technology.

**For more information, performance and warranty guidelines please contact your local Drytac office.**

© 2025 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	White Matte Polypropylene (PP) or Clear Gloss Polypropylene (PP)
<b>Adhesive</b>	Clear Removable Dot Pattern Polyacrylate
<b>Release Liner</b>	Hybrid PE liner

### PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	3.7 mil (92µ)
<b>Adhesive Layer</b>	1.1 mil (28µ)
<b>Outdoor Durability</b>	6 Months
<b>Application Temperature</b>	>41°F (5°C)
<b>Service Temperature Range</b>	-4°F to 203°F (-20°C to 95°C)
<b>Shelf Life</b>	2 Years
<b>Storage Conditions</b>	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity



#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013