

# SpotOn®

## SynTac™

SpotOn® SynTac™ is a 3.7 mil (92 $\mu$ ) white matte or clear gloss polypropylene (PP) film designed for effortless, tool-free installation. Its innovative dot-patterned, removable polyacrylate adhesive allows for bubble-free application on a wide range of surfaces, and it can be cleanly removed within 12 months.

Developed with sustainability in mind, SpotOn SynTac is perfect for seasonal promotions, short-term campaigns, or peel-and-stick signage where easy removal is key.

### Product Codes:

**SPOS** - SpotOn SynTac White Matte  
**SPOX** - SpotOn SynTac Clear Gloss

**92** micron White Matte or  
Clear Gloss Polypropylene (PP)



Latex\*/Resin  
UV



Removable  
Dot Pattern Polyacrylate  
Adhesive



Width 1370mm



INTERIOR



EXTERIOR

## EASY TO APPLY AND ECO-FRIENDLY



## APPLICATIONS

WINDOW GRAPHICS

WALL GRAPHICS

RETAIL SPACES

EVENT SIGNAGE

DRYTAC®  
**ZERO**®

# SpotOn®

## SynTac™

SpotOn® SynTac™ is a 3.7 mil (92 $\mu$ ) printable matte white or gloss clear polypropylene film featuring a removable, dot-pattern pressure-sensitive polyacrylate adhesive. Protected by a single-sided, siliconized hybrid PE-coated release liner, this eco-conscious, ink-receptive synthetic film is ideal for indoor and short-term outdoor applications where easy installation and clean removal are essential.

### ● TOOL-FREE, BUBBLE-FREE APPLICATION

Thanks to its dot-pattern adhesive, SpotOn SynTac installs effortlessly without the need for tools or professional installers.

### ● ECO-CONSCIOUS AND PVC-FREE

Made from polypropylene, this film offers a sustainable alternative to traditional PVC graphics media—ideal for environmentally focused projects.

### ● VERSATILE & REMOVABLE

Perfect for both indoor and short-term outdoor applications, SpotOn SynTac removes cleanly within 12 months, leaving no residue behind.

\*Latex Ink Compatibility Note: For optimal results, use with HP Latex 4th generation ink technology.

**For more information,  
performance and warranty  
guidelines please contact your  
local Drytac office.**

© 2026 Drytac Corporation. E&OE.  
All other trademarks are the property  
of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

Film	White Matte Polypropylene (PP) or Clear Gloss Polypropylene (PP)
Adhesive	Clear Removable Dot Pattern Polyacrylate
Release Liner	Hybrid PE liner

### PRODUCT CHARACTERISTICS

Film Thickness	3.7 mil (92 $\mu$ )
Adhesive Layer	1.1 mil (28 $\mu$ )
Outdoor Durability	6 Months
Fire Rating	B-s1,d0 (EN13501-1)
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)
Shelf Life	2 Years
Storage Conditions	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity



#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013