

# FloorTac™

## Emerytex® White RB

ONE PART FLOOR GRAPHIC SOLUTION

FloorTac™ Emerytex® White RB is designed for one step, slip-rated floor graphics. Its removable, non-damaging adhesive makes FloorTac™ Emerytex® White RB ideal for short-term indoor advertising where graphics are applied to the floor. It is ideal for public environments where safety is a top priority.

### CAN BE APPLIED TO:

- CERAMIC TILES
- SEALED WOOD
- CONCRETE
- WAXED VINYL
- MARBLE
- TERRAZZO
- SHORT-PILE CARPET\*\*\*

Part Number: PFTE

8.0  
mil

Textured White  
Monomeric  
PVC

Matte



(Eco) Solvent\*\*  
Latex  
UV



Removable  
Gray Acrylic  
(Pressure Sensitive)



Widths up to 54 in



MONTHS DURABILITY  
UP TO  
**9**  
MONTHS  
INTERIOR\*



### APPLICATIONS

SCHOOLS  
HOSPITALS  
RETAIL ADVERTISING  
SUPERMARKETS  
RESTAURANTS



**DRYTAC®**  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

# FloorTac™

## Emerytex® White RB

FloorTac™ Emerytex® White RB is a 8 mil (200µ) monomeric soft calendared white PVC film with a matte pebble textured finish, coated on one side with a pressure sensitive removable acrylic adhesive that is protected by a bleached Kraft release paper coated on both sides with PE and siliconized on the release side. The textured emboss on the film provides slip resistance.

- IDEAL FOR SHORT-TERM INDOOR FLOOR GRAPHICS
- SLIP & FIRE RATED SINGLE PART FLOOR GRAPHIC SOLUTION
- FOR BEST RESULTS, LEAVE A 0.25" (6MM) NON-PRINTED BORDER AROUND THE EDGE OF THE IMAGE.

\* Up to 9 months indoor durability dependent upon floor-traffic and correct installation.

\*\*\*The carpet installation surface must be short pile or tightly woven, minimal texture with a limited cushion. The carpet should be clean and dry prior to application. Due to the huge variance of carpet surfaces, materials and types along with pre and post chemical treatments, a test sample is mandatory prior to production and installation. It is important that all printer and ink manufacturer guidelines are followed. The Drytac limited warranty only covers for material defect, no returns or consequential losses will be accepted.

**For more information, performance and warranty guidelines please contact your local Drytac office.**

© 2020 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Matte White Pebble Textured Monomeric Soft Calendared PVC
<b>Adhesive</b>	Removable Gray Acrylic (Pressure Sensitive)
<b>Release Liner</b>	2 Side PE Coated, 1 Side Siliconised Kraft

### PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	8 mil (200µ)   9.4 mil
<b>Adhesive Layer</b>	1.4 mil (35µ)   (235µ)
<b>Fire Rating</b>	Class 1 or Class A (ASTM E84)
<b>Slip Certifications</b>	Moderate Slip Potential (HB198:2014 (AS/NZS 4586)) PASS (ANSI B101.3) <i>interior dry areas that are contaminant free</i>
<b>Application Temperature</b>	>-4°F (-20°C)
<b>Service Temperature Range</b>	-58°F to 212°F (-50°C to 100°C)
<b>Shelf Life</b>	1 year
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

### \*\*PRINTING RECOMMENDATIONS

UV and Latex inks offer the greatest durability for floor applications. Due to the variance of solvent inks it is recommended scuff resistance is tested prior to installation.

**DRYTAC®**  
**ADHESIVE SCIENCE**

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013