

Polar®

SandTac Floor

Polar® SandTac Floor is designed for eye-catching floor graphics that instantly attract attention. Its removable, non-damaging adhesive makes Polar® SandTac Floor ideal for short-term indoor advertising where graphics are applied to the floor. It is slip-rated, making it ideal for public environments where safety is a top priority.

CAN BE APPLIED TO

- CERAMIC TILES
- SEALED WOOD
- SMOOTH CONCRETE
- WAXED VINYL
- MARBLE OR TERRAZZO
- SHORT-TERM CARPET GRAPHICS***

7.0
mil

Textured White
Monomeric
PVC

Matte



(Eco) Solvent**
Latex
UV



Removable
Solvent Acrylic
(Pressure Sensitive)



Widths up to 60 in



INTERIOR*

ONE PART SLIP-RATED FLOOR GRAPHIC SOLUTION



APPLICATIONS

SCHOOLS

HOSPITALS

RETAIL ADVERTISING

SUPERMARKETS

RESTAURANTS



DRYTAC®

ADHESIVE SCIENCE

www.drytac.com

Polar®

SandTac Floor

Polar® SandTac Floor is a 7 mil (175µ) printable, matte white PVC film with a removable, solvent pressure sensitive acrylic adhesive protected by a 2 side PE coated release liner. The textured emboss on the film provides excellent slip resistance.

- SLIP RATED SINGLE PART FLOOR GRAPHIC SOLUTION
- FOR BEST RESULTS, LEAVE A 0.25" (6MM) NON-PRINTED BORDER AROUND THE EDGE OF THE IMAGE.

* Up to 6 months indoor durability dependent upon floor-traffic and correct installation.

***If installed to carpet, the carpet installation surface must be short pile or tightly woven, minimal texture with a limited cushion. The carpet should be clean and dry prior to application. Due to the huge variance of carpet surfaces, materials and types along with pre and post chemical treatments, a test sample is mandatory prior to production and installation. It is important that all printer and ink manufacturer guidelines are followed. The Drytac limited warranty only covers for material defect, no returns or consequential losses will be accepted.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Textured Matte White PVC
Adhesive	Removable Solvent Acrylic (Pressure Sensitive)
Release Liner	2 Side PE Coated Liner

PRODUCT CHARACTERISTICS

Film Thickness	7.0 mil (175µ)	8.4 mil (210µ)
Adhesive Layer	1.4 mil (35µ)	
Slip Rating	<ul style="list-style-type: none">• Moderate Slip Potential; Wet: 34 (EN 13036-4/ASTM E303)• R10 (DIN 51130)• PASS (ANSI A137.1/A326.3) <i>interior dry areas that are contaminant free</i>	
Fire Rating	B1 (DIN 4102-1)	
Application Temperature	>-4°F (-20°C)	
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)	
Shelf Life	2 years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

**PRINTING RECOMMENDATIONS

UV and Latex inks offer the greatest durability for floor applications. Due to the variance of solvent inks it is recommended scuff resistance is tested prior to installation.

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com