

Polar®

SandTac Floor

Polar® SandTac Floor is designed for eye-catching floor graphics that instantly attract attention. Its removable, non-damaging adhesive makes Polar® SandTac Floor ideal for short-term indoor advertising where graphics are applied to the floor. It is slip-rated, making it ideal for public environments where safety is a top priority.

CAN BE APPLIED TO

- CERAMIC TILES
- SEALED WOOD
- SMOOTH CONCRETE
- WAXED VINYL
- MARBLE OR TERRAZZO

7.0
mil

Textured White
Monomeric
PVC

■
Matte



(Eco) Solvent**
Latex
UV



Removable
Solvent Acrylic
(Pressure Sensitive)



Widths up to 60 in



MONTHS DURABILITY
UP TO
6
MONTHS DURABILITY
INTERIOR*

ONE PART SLIP-RATED FLOOR GRAPHIC SOLUTION



APPLICATIONS

SCHOOLS
HOSPITALS
RETAIL ADVERTISING
SUPERMARKETS
RESTAURANTS



DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

Polar[®]

SandTac Floor

Polar[®] SandTac Floor is a 7 mil (175µ) printable, matte white PVC film with a removable, solvent pressure sensitive acrylic adhesive protected by a 2 side PE coated release liner. The textured emboss on the film provides excellent slip resistance.

- IDEAL FOR SHORT-TERM INDOOR FLOOR GRAPHICS
- SLIP RATED SINGLE PART FLOOR GRAPHIC SOLUTION
- FOR BEST RESULTS, LEAVE A 0.25" (6MM) NON-PRINTED BORDER AROUND THE EDGE OF THE IMAGE.

* Up to 6 months indoor durability dependent upon floor-traffic and correct installation.

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

| | |
|----------------------|--|
| Film | Textured Matte White PVC |
| Adhesive | Removable Solvent Acrylic (Pressure Sensitive) |
| Release Liner | 2 Side PE Coated Liner |

PRODUCT CHARACTERISTICS

| | | |
|----------------------------------|---|-------------------|
| Film Thickness | 7.0 mil (175µ) | 8.4 mil (210µ) |
| Adhesive Layer | 1.4 mil (35µ) | |
| Slip Rating | R10 (DIN 51130) PASS (ANSI A137.1/A326.3) <i>interior dry areas that are contaminant free</i> | |
| Fire Rating | B1 (DIN 4102-1) | |
| Application Temperature | >-4°F (-20°C) | |
| Service Temperature Range | -4°F to 203°F (-20°C to 95°C) | |
| Shelf Life | 2 years | |
| Storage Conditions | 59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity | |

**PRINTING RECOMMENDATIONS

UV and Latex inks offer the greatest durability for floor applications. Due to the variance of solvent inks it is recommended scuff resistance is tested prior to installation.

DRYTAC[®]

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com