

## SLIP RATING - THIRD PARTY CERTIFICATION

|                                   |   |
|-----------------------------------|---|
| <b>PRODUCT NAME:</b>              | Dynamic™ Sandgrain                                      |
| <b>PRODUCT PART NUMBER:</b>       | LFC-S   |
| <b>STANDARD:</b>                  | EN 13036-4  |
| <b>PENDULUM TEST VALUE (PTV):</b> | Dry: 77<br>Wet: 30                                      |
| <b>CLASSIFICATION:</b>            | Dry: Low Slip Potential<br>Wet: Moderate Slip Potential |
| <b>ISSUE DATE:</b>                | April 2020  |
| <b>TEST REPORT REFERENCE:</b>     | UK201731-13170  |

**For more information, performance and warranty guide lines please contact your local Drytac office.**

These test results are not transferable and may not be relevant or applicable to real life applications. Therefore, Drytac<sup>®</sup> strongly recommends and other regulatory entities may require additional testing to determine the suitability for any specific end application. Refer to Drytac<sup>®</sup> Terms and Conditions of Sale at [www.drytac.com](http://www.drytac.com) for additional liability limitations. This certificate is the property of Drytac<sup>®</sup> Corporation. This certificate and all copies should be returned to Drytac<sup>®</sup> upon request.

# DRYTAC<sup>®</sup>