

Interlam™

Pro Gloss

Interlam™ Pro Gloss is a 70µ (2.8 mil) monomeric soft calendared PVC laminating film with a Gloss finish, coated on one side with a pressure sensitive, aqueous acrylic adhesive.

- RECOMMENDED FOR INTERIOR AND EXTERIOR USE ON FLEXIBLE MEDIA SUBSTRATES WHERE A GLOSS FINISH IS REQUIRED
- IDEAL FOR POP DISPLAYS, ARCHITECTURAL RENDERINGS, PROMOTIONAL DISPLAYS, AND EVENT SIGNAGE
- INTERLAM™ PRO GLOSS HAS A CLASS 0 FIRE RATING ACCORDING TO UK STANDARDS FOR SURFACE SPREAD OF FLAME, MAKING IT PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS, SUCH AS AIRPORTS, HOTELS AND HOSPITALS.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2019 Drytac Corporation. E&OE. All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Gloss Monomeric Soft Calendared PVC
Adhesive	Acrylic (Pressure Sensitive)
Release Liner	1 Side PE Coated, 1 Side Siliconised Kraft

PRODUCT CHARACTERISTIC

Film Thickness	3.0 mil (75µ) 4.0 mil (100µ)
Adhesive Layer	1 mil (25µ)
Film/Adhesive Ratio	2.8:1
UV Protection	Yes
Outdoor Durability	5 Years (Ink Dependent)
Fire Rating	Class 0
Application Temperature	-4°F (-20°C)
Service Temperature Range	-49°F to 230°F (-45°C to +110°C)
Peel Strength (20 min, FTM1)	11 N/25mm
Shelf Life	2 Years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013