

Polar®

Choice White

Polar® Choice White is the ideal choice for a printable monomeric PVC film. Available with a gloss or matte finish and permanent or removable adhesive, Polar® Choice White maximises adhesive performance on a wide variety of substrates.

Polar® Choice White is outdoor durable for up to 5 years and is ideal for signage and general advertising applications, including windows, POP displays, stickers and decals.


- IDEAL FOR INDOOR & OUTDOOR GENERAL SIGNAGE & DISPLAY
- WINDOW & WALL GRAPHICS
- SUITABLE FOR MANY APPLICATIONS


Product Codes:


CGWG - Polar Choice White Gloss PB


CPWG - Polar Choice White Gloss P

CRWM - Polar Choice White Matte RB

80 White Monomeric PVC
micron  Gloss or Matte


 (Eco)Solvent Latex UV

 Permanent or Removable Acrylic Solvent Adhesive

 Widths up to 1524mm

 **5** YEARS DURABILITY **INTERIOR & EXTERIOR**
(unprinted)

THE CHOICE FOR MONOMERIC PVC



APPLICATIONS

- GENERAL SIGNAGE
- WINDOW GRAPHICS
- EXHIBITION GRAPHICS
- POS DISPLAY



DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

Polar[®]

Choice White

Polar[®] Choice White films are 80 μ (3.2 mil) gloss or matte white monomeric PVC films, coated on one side with a permanent or removable, pressure sensitive clear or grey solvent acrylic adhesive that is protected by a 140gsm 2 side PE coated release liner. Suitable for interior and exterior use (up to 5 years).

CGWG - Polar Choice White Gloss PB

White Gloss film with Permanent Grey Adhesive

CPWG - Polar Choice White Gloss P

White Gloss film with Permanent Clear Adhesive

CRWM - Polar Choice White Matte RB

White Matte film with Removable Grey Adhesive

- IDEAL FOR GENERAL SIGNAGE & GRAPHIC PROMOTIONS
- SUITABLE FOR INTERIOR AND EXTERIOR USE
- CAN BE APPLIED TO MANY SMOOTH SURFACES

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	White Gloss or Matte Monomeric PVC
Adhesive	Clear or Grey Permanent or Grey Removable Solvent Acrylic (Pressure Sensitive)
Release Liner	140gsm 2 side PE Coated Release Paper

PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil (80 μ) 4.2 mil (105 μ)
Adhesive Layer	1 mil (25 μ) (105 μ)
Outdoor Durability	5 Years (Unprinted)
Fire Rating (EN 13501-1)	Class B
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

OVERLAMINATE RECOMMENDATIONS

When using Polar[®] Choice, an overlamine can be used for maximum life expectancy. Products recommended for use with Polar[®] Choice are Drytac's Dynamic[™], Interlam[™] or Protac[™] overlaminates.

DRYTAC[®]

ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com