

# SynTac®

## Air LB

SynTac® Air LB is a white matte polypropylene film with a gray low initial tack removable adhesive with bubble-free technology. This high quality, UV printable white synthetic paper was specifically developed with the environment in mind and is ideal for short-term POP retail and hospitality window and wall graphics.

- SYNTAC AIR LB HAS A LOW-TACK REMOVABLE ADHESIVE PAIRED WITH AN AIR EGRESS RELEASE LINER FOR EASY, BUBBLE-FREE GRAPHIC APPLICATION
- SYNTAC AIR LB IS A RECYCLABLE FILM WHERE FACILITIES EXIST



PRODUCT CODE: SALB

**3.0**  
mil

Smooth  
White  
PP



Matte



UV



Low-Tack Grey  
Removable Adhesive with  
Bubble-Free Technology



Widths up to 54 in

YEARS DURABILITY  
**3**

INTERIOR

YEARS DURABILITY  
**2**

EXTERIOR

EASY TO APPLY, BUBBLE-FREE GRAPHICS



## APPLICATIONS

Window & Wall Graphics  
Retail Promotions  
POS Advertising  
Decals & Stickers



DRYTAC®  
**ZERO**

[www.drytac.com](http://www.drytac.com)

# SynTac®

## Air LB

SynTac® Air LB is a 3.0 mil (75µ) printable white matte PP film, coated on one side with a grey low tack removable water-based adhesive protected with a 2 side PE coated Kraft textured release liner with a bubble-free technology ideal for easy installations. The product offers a pressure sensitive adhesive with low initial tack, tinted to provide excellent opaque characteristics.

- **IDEAL FOR EASY TO APPLY RETAIL AND POP WINDOW AND WALL GRAPHICS**
- **SYNTAC AIR LB IS COMPATIBLE WITH UV INKJET TECHNOLOGY**

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2022 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATIONS

### PRODUCT STRUCTURE

<b>Film</b>	Matte White PP
<b>Adhesive</b>	Grey Low Tack Removable Acrylic (Pressure Sensitive)
<b>Release Liner</b>	2 Sided PE Coated Kraft Paper with Bubble-Free Technology

### PRODUCT CHARACTERISTICS

<b>Film Thickness</b>	3.0 mil (75µ)	4.2 mil (105µ)
<b>Adhesive Layer</b>	1.2 mil (30µ)	
<b>Outdoor Durability</b>	2 Years	
<b>Application Temperature</b>	>41°F (5°C)	
<b>Service Temperature Range</b>	-20°F to 200°F (-29°C to 93°C)	
<b>Shelf Life</b>	2 Years	
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	



#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401-B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013