

Polar®

Grip Air

Polar® Grip Air's unique high bond adhesive is designed to stick to products with low surface energy, making it suitable for adhering graphics or decals to machine equipment, motorcycle helmets, Sintra®, smooth plastic substrates or coarse surfaces such as brick or concrete. Unlike most self-adhesive vinyls, Polar® Grip Air has a thicker adhesive layer that creates a tighter grip on porous materials. Polar® Grip Air has an air release liner that provides bubble-free and easy graphic application.

- IDEAL FOR GRAPHICS OR DECALS ON MACHINE EQUIPMENT
- SUITABLE FOR INDOOR & OUTDOOR USE
- THE AGGRESSIVE ADHESIVE IS IDEAL FOR LOW SURFACE ENERGY SUBSTRATES
- BONDS WELL TO BRICK OR COARSE CONCRETE SURFACES WITH HEAT

Product Code: PGMA

80
micron

White
Polymeric
PVC

Matte



(Eco) Solvent
Latex
UV



High Coat Weight Grey
Permanent Adhesive with
Bubble-Free Technology



Widths up to 1370mm



INTERIOR & EXTERIOR
(with matching overlamine)

HIGH TACK ADHESIVE WITH BUBBLE-FREE TECHNOLOGY



APPLICATIONS

MACHINERY SIGNAGE
LOW ENERGY SUBSTRATES
MOTORCYCLE HELMETS
BRICK WALLS



DRYTAC®
ADHESIVE SCIENCE

www.drytac.com

Polar®

Grip Air

Polar® Grip Air is a 3.2 mil (80µ) premium, white polymeric self-adhesive PVC film with a high coat weight, permanent, pressure sensitive grey acrylic adhesive that is protected by a 90# white Kraft release paper with bubble-free technology which makes for an easy install. The film's unique aggressive adhesive makes it suitable for graphic applications where flexibility and high bond adhesion are desired.

- THE AGGRESSIVE ADHESIVE IS IDEAL FOR LOW SURFACE ENERGY SUBSTRATES
- SUITABLE FOR INDOOR & OUTDOOR USE
- GREAT FLEXIBILITY AND HIGH BOND ADHESION

INSTALLATION RECOMMENDATION

The surface must be clean and free of defects before application. Please refer to the application guide for use on rough surfaces.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2024 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

10032024

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte White Polymeric PVC
Adhesive	High Coat Weight Grey Permanent Acrylic (Pressure Sensitive)
Release Liner	90# PE Coated with Bubble-Free Technology

PRODUCT CHARACTERISTICS

Film Thickness	3.2 mil (80µ) 4.6 mil (116.84µ µ)
Adhesive Layer	1.4 mil (35µ)
Outdoor Durability	7 years with matching laminate
Fire Ratings	Class C -s1,d0 (EN 13501-1) Class A or 1 (ASTM E-84) PASS (CAN/ULC-S102)
Paired Solution Fire Rating	B _f - s1 (EN 13501-1) when paired with Interlam Pro Emerytex
Application Temperature	>-5°F (-20°C)
Service Temperature Range	-49°F to 230°F (-45°C to 110°C)
Shelf Life	2 Years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

OVERLAMINATE RECOMMENDATIONS

When using Polar® Grip Air, an overlaminate can be used for maximum life expectancy. Products recommended for use with Polar® Grip Air are Drytac's Weathershield™, Protac™ and Interlam™ Pro overlaminates.

For floor graphics, it is recommended to use a slip certified overlaminate such as Drytac's Interlam™ Emerytex® or Protac™ Scuffguard™.

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com

Polar®

Grip Air Matte

WELCOME TO THE
WINTER WORLD GAMES

APPLICATIONS

- Machine Equipment
- Motorcycle Helmets
- Low Surface Energy Surfaces
- Brick and Concrete Surfaces

Product Code: PGMA

80 White
micron Polymeric
PVC


Matte



(Eco) Solvent
Latex
UV



High Coat Weight Grey
Permanent Adhesive with
Bubble-Free Technology



Widths up to 1370 mm



7 YEARS DURABILITY
INTERIOR & EXTERIOR
(with matching overlamine)

For more technical information,
please refer to www.drytac.com.



LEARN MORE

DRYTAC®
ADHESIVE SCIENCE

www.drytac.com