

PaperTac™

White Matte

PaperTac™ White Matte is a premium coated paper with clear permanent adhesive, ideal for retail promotion, advertising, events, and more. Designed for exceptional print quality across a range of printers—including aqueous, latex/resin, and UV—this versatile media delivers stunning photorealistic prints, making it perfect for short-term applications and eco-conscious projects.

Engineered for durability, PaperTac™ White Matte features water-repellent and scratch-resistant properties, ensuring long-lasting indoor performance. Its clear permanent adhesive allows for easy mounting to rigid card substrates, eliminating the need for a flatbed printer when creating printed boards.

For brands and print professionals seeking a sustainable solution without compromising on quality, PaperTac™ White Matte delivers the perfect balance of performance and eco-responsibility.

Product Code: PTC

140
gsm

Coated
Paper



Aqueous
Latex/Resin
UV



Clear Permanent
Acrylic
Adhesive



Widths up to 1250mm



INTERIOR

ADHESIVE PAPER FOR VIBRANT PRINTS



APPLICATIONS

RETAIL PROMOTIONS

EVENT GRAPHICS

MOUNT TO BOARDS



DRYTAC®
ZERO®

PaperTac™

White Matte

PaperTac™ White Matte is a high-quality 140gsm matte-coated paper designed for wide color gamut aqueous printers, and is also suitable for use on latex/resin, and UV printers. This versatile media is ideal for photorealistic prints, short-term advertising, and other eco-friendly applications. Its water-repellent and scratch-resistant properties ensure durability for indoor use.

Featuring a clear permanent adhesive, PaperTac™ can be easily mounted to rigid card substrates, allowing users to create printed boards without the need for a flatbed printer. It is backed by a 100gsm double-sided PE Kraft siliconized release liner, ensuring smooth handling and application.

PaperTac™ is an eco-conscious solution, catering to the growing demand for sustainable print media without compromising on print quality and performance.

PaperTac White Matte is a Best-in-Class solution designed for easy recycling—both the paper face film and adhesive can be recycled together with no visual or adhesion issues. It achieves a 91/100 recyclability score using the CEPI Recyclability Test Method v2 (Oct 2022).

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2026 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATIONS

PRODUCT STRUCTURE

Film Matte Coated Paper

Adhesive Clear Permanent Water Based (Acrylic)

Release Liner 100 gsm 2 Sided PE Siliconised Kraft

PRODUCT CHARACTERISTICS

Film Thickness 140 gsm

Adhesive Layer 0.6 mil (14μ)

Outdoor Durability Not Applicable

CEPI Recyclability Score 91/100 - Best In Class

Application Temperature >41°F (5°C)

Service Temperature Range 41°F to 104°F (5°C to 40°C)

Shelf Life 2 Years

Storage Conditions 59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity



Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013