

PrintDuo™

Push/Pull

DOUBLE-SIDED PRINTABLE

PrintDuo™ is a premium double-sided printable white matte multilayered polypropylene and polyester film. The bright white surface of PrintDuo™ enhances vibrant color reproduction, ensuring crisp, sharp visuals and text that pop. Whether for indoor banner stands, roll-up displays, point-of-sale setups, or trade show graphics, it delivers professional, high-resolution results. It's also resistant to tearing and abrasion, ensuring your displays maintain their impressive look even in demanding environments.

What truly sets PrintDuo apart is its compatibility with Drytac's mounting adhesives such as SpotOn Duo, ReTac Duo and WindowTac. When paired, PrintDuo allows for the creation of double-sided window graphics that are easy to apply and reposition, thanks to the adhesive's combination of permanent and removable sides.

PRODUCT CODE: PRD

10
mil

**Multilayered
Polypropylene
and Polyester Blend**  **Matte**



**(Eco) Solvent
Latex/Resin
UV**



**Adhesive
Free**



Widths up to 60 in



INTERIOR



EXTERIOR



APPLICATIONS

WINDOW GRAPHICS

WALL GRAPHICS

POS DISPLAY

HANGING BANNERS



www.drytac.com

PrintDuo is a premium 10 mil (250µ) double-sided white matte blockout media, offering a PVC-free alternative for high-quality prints. Its unique composition of multilayered polypropylene and polyester provides exceptional strength and light-blocking properties, making it ideal for high-traffic commercial events, promotions, and display presentations.

- **DOUBLE-SIDED PRINTABLE:**
IDEAL FOR CREATING IMPACTFUL, DUAL-SIDED DISPLAYS WITH VIBRANT COLORS AND SHARP DETAIL.
- **PVC-FREE CONSTRUCTION:**
ENVIRONMENTALLY FRIENDLY, USING A BLEND OF POLYPROPYLENE AND POLYESTER FOR SUSTAINABLE SIGNAGE.
- **DURABLE & TEAR-RESISTANT:**
BUILT TO WITHSTAND DEMANDING ENVIRONMENTS WITHOUT SACRIFICING PRINT QUALITY.
- **HIGH DIMENSIONAL STABILITY:**
ENSURES ACCURATE, WARP-FREE PRINTING FOR LONG-LASTING DISPLAYS.

PRODUCT STRUCTURE

Film	Multilayered Polypropylene and Polyester Blend
------	--

PRODUCT CHARACTERISTICS

Film Thickness	10 mil (250µ)
----------------	---------------

Finish	Matte
--------	-------

Opacity	100%
---------	------

Outdoor Durability	2 Years
--------------------	---------

Service Temperature Range	-4°F to 146°F (-20°C to 63°C)
---------------------------	-------------------------------

Shelf Life	2 Years
------------	---------

Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity
--------------------	--

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2025 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.



Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013