

CTac™ 150

Air

CTac™ 150 Air is a reliable white monomeric PVC film line designed for consistent print quality and effortless installation. Its advanced air-release adhesive technology enables smooth, bubble-free application, reducing install time and improving overall performance.

Available in a matte finish with either a clear permanent or clear removable adhesive, CTac™ 150 Air delivers dependable adhesion and user-friendly handling across a wide range of smooth substrates. With up to 3 years of outdoor durability, it's ideal for signage, window graphics, POP displays,

Product Codes:

CSMPA - CTac 150 Air White P

White Matte Film with Permanent Clear Adhesive

CSMRA - CTac 150 Air White R

White Matte Film with Removable Clear Adhesive

6.0
mil

White
Monomeric
PVC



Matte



(Eco) Solvent
Latex/Resin
UV



Clear
Permanent or Removable
Acrylic Solvent Adhesive



Widths up to 60 in



INTERIOR & EXTERIOR

EVERYDAY SIGNAGE AND GRAPHICS



APPLICATIONS

GENERAL SIGNAGE

WINDOW GRAPHICS

EXHIBITION GRAPHICS

POS DISPLAY



DRYTAC®

ADHESIVE SCIENCE

www.drytac.com

CTac™ 150

Air

CTac™ 150 Air films are 6.0 mil (150µ) matte white monomeric PVC films, coated on one side with a clear permanent or removable pressure sensitive solvent acrylic adhesive that is protected by a 140gsm 2 side PE coated release liner with bubble-free technology. Suitable for interior and exterior use (up to 3 years).

Product Codes:

CSMPA - CTac 150 Air White P

White Matte Film with Permanent Clear Adhesive

CSMRA - CTac 150 Air White R

White Matte Film with Removable Clear Adhesive

- IDEAL FOR GENERAL SIGNAGE & GRAPHIC PROMOTIONS
- SUITABLE FOR INTERIOR AND EXTERIOR USE
- CAN BE APPLIED TO MANY SMOOTH SURFACES

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2025 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

11242025

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte Monomeric PVC
Adhesive	Clear Permanent or Removable Solvent Acrylic (Pressure Sensitive)
Release Liner	140 gsm 2 Side PE Coated, 1 Side Siliconized White Kraft with Bubble-Free Technology

PRODUCT CHARACTERISTICS

Film Thickness	6.0 mil (150µ)	7.0 mil (175µ)
Adhesive Layer	1 mil (25µ)	
Outdoor Durability	3 Years	
Application Temperature	>41°F (5°C)	
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)	
Shelf Life	2 years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com