

CTac™ 80

White

CTac™ 80 is a dependable white monomeric PVC film line engineered for consistent print quality and smooth application. Available in a matte finish with either a clear permanent or clear removable adhesive, CTac™ 80 delivers strong adhesion and clean removability across a wide range of smooth substrates.

With outdoor durability of up to 3 years, CTac™ 80 is ideal for signage, window graphics, POP displays, stickers, decals, and general advertising applications that require a cost-effective, easy-to-apply solution.

Product Codes:

CMP - CTac 80 White Matte P

White Matte Film with Permanent Clear Adhesive

CMR - CTac 80 White Matte R

White Matte Film with Removable Clear Adhesive

3.2
mil

White
Monomeric
PVC



Matte



(Eco) Solvent
Latex
UV



Clear
Permanent or Removable
Acrylic Solvent Adhesive



Widths up to 54 in



INTERIOR & EXTERIOR

EVERYDAY SIGNAGE AND GRAPHICS



APPLICATIONS

GENERAL SIGNAGE

WINDOW GRAPHICS

EXHIBITION GRAPHICS

POS DISPLAY



DRYTAC
ADHESIVE SCIENCE

www.drytac.com

CTac™ 80

White

CTac™ 80 films are 3.2 mil (80µ) matte white monomeric PVC films, coated on one side with a clear permanent or removable pressure sensitive solvent acrylic adhesive that is protected by a 140gsm 2 side PE coated release liner. Suitable for interior and exterior use (up to 3 years).

Product Codes:

CMP - CTac 80 White Matte P

White Matte Film with Permanent Clear Adhesive

CMR - CTac 80 White Matte R

White Matte Film with Removable Clear Adhesive

- IDEAL FOR GENERAL SIGNAGE & GRAPHIC PROMOTIONS
- SUITABLE FOR INTERIOR AND EXTERIOR USE
- CAN BE APPLIED TO MANY SMOOTH SURFACES

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2025 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

11/20/2025

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte Monomeric PVC
Adhesive	Clear Permanent or Removable Solvent Acrylic (Pressure Sensitive)
Release Liner	140 gsm 2 Side PE Coated, 1 Side Siliconized White Kraft

PRODUCT CHARACTERISTIC

Film Thickness	3.2 mil (80µ)	4.2 mil (105µ)
Adhesive Layer	1 mil (25µ)	
Outdoor Durability	3 Years	
Application Temperature	>41°F (5°C)	
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)	
Shelf Life	2 years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

OVERLAMINATE RECOMMENDATIONS

When using CTac™ 80, an overlamine can be used for maximum life expectancy. Products recommended for use with CTac™ 80 are Drytac's Dynamic™ Plus, Interlam™ Pro or Protac™ overlaminates.

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com