

Transit

Air RB

Transit Air RB is a high-quality, 3.2 mil white monomeric PVC film designed for short- to medium-term transit and fleet graphics. Its smooth, matte finish makes it ideal for flat vehicle sides, arena displays, and other applications where quick, clean installations are required. The grey removable adhesive ensures strong initial tack while allowing easy removal without residue, making it perfect for temporary graphics.

For smooth, flat surfaces and hassle-free installation, Transit Air RB features a grey, moisture-stable adhesive combined with bubble-free technology, helping installers achieve a smooth, professional finish with minimal effort. Its removable adhesive and durable film make it a reliable choice for temporary transit, fleet, and arena graphics.

Product Code: TRA

3.2
mil White
Monomeric
PVC



Matte



(Eco) Solvent
Latex/Resin
UV



Moisture Stable Grey
Removable Adhesive with
Bubble-Free Technology



Widths up to 61 in



INTERIOR AND EXTERIOR

BUBBLE-FREE TRANSIT GRAPHICS



APPLICATIONS

TRANSIT ADVERTISING

ARENA ADVERTISING

GENERAL SIGNAGE

DRYTAC[®]

ADHESIVE SCIENCE

www.drytac.com

Transit

Air RB

Transit Air RB is a 3.2mil (80µ) white matte monomeric PVC film featuring a moisture-stable grey removable adhesive, designed for easy application and clean removal. The adhesive is protected by a 140gsm two-sided PE coated release liner with bubble-free technology for effortless installation.

With an outdoor durability of up to four years, Transit Air RB performs reliably across flat transit applications, arena advertising, and other short- to mid-term promotional graphics.

- IDEAL FOR TRANSIT, FLEET, AND ARENA GRAPHICS
- BUBBLE-FREE INSTALLATION ON FLAT SURFACES
- REMOVABLE ADHESIVE FOR CLEAN REMOVAL

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2025 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

11112025

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	White Matte Monomeric PVC
Adhesive	Moisture Stable Grey Removable Acrylic
Release Liner	140gsm 2 Side PE Coated Paper with Bubble-Free Technology

PRODUCT CHARACTERISTICS

Film Thickness	3.2 mil (80µ)
Adhesive Layer	1.0 mil (25µ)
Outdoor Durability	4 Years (unprinted)
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)
Shelf Life	2 Years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

DRYTAC
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com