

ViziPrint®

Select Clear R

ViziPrint® Select Clear R is a premium optically clear printable polyester (PET) film engineered for high-impact window graphics and surface applications where clarity matters most. Featuring a 4.6 mil (115µ) gloss PET face film and an optically clear removable adhesive, it delivers sharp image quality, strong visual depth, and a clean, professional finish on glass and other smooth, flat substrates.

Designed for dependable performance indoors and out, ViziPrint® Select Clear R offers excellent print compatibility with latex/resin, and UV technologies, along with easy application and clean removability for up to 12 months. With long-term interior durability and short-term exterior performance, it is ideal for retail window graphics, decals, displays, and interior décor applications across retail and hospitality environments.

Product Code: VSR

115 Optically
Clear
micron Polyester (PET)



Latex/Resin
UV



Removable
Optically Clear
Adhesive



Width 1520mm



7 YEARS DURABILITY
INTERIOR



2 YEARS DURABILITY
EXTERIOR

OPTICALLY CLEAR REMOVABLE GRAPHICS



APPLICATIONS

WINDOW GRAPHICS

RETAIL SPACES

INTERIOR DÉCOR

HOSPITALITY/HOTELS



www.drytac.com

ViziPrint®

Select Clear R

ViziPrint® Select Clear R is an optically clear PET film with an optically clear removable adhesive, protected by a clear polyester release liner. Engineered for high-quality window graphics and display applications, it delivers outstanding visual clarity, reliable adhesion, and smooth application across a wide service temperature range. The film removes cleanly and without residue for up to 12 months, making it ideal for retail, décor, and promotional graphics.

● OPTICALLY CLEAR FILM

Engineered with a gloss PET face film and optically clear solvent-acrylic removable adhesive, ViziPrint Select Clear R delivers exceptional image clarity and a clean, high-end appearance on glass and other smooth surfaces.

● ECO-CONSCIOUS AND PVC-FREE

Made from polyester, this film offers a sustainable alternative to traditional PVC graphics media—ideal for environmentally focused projects.

**For more information,
performance and warranty
guidelines please contact your
local Drytac office.**

© 2026 Drytac Corporation. E&OE.
All other trademarks are the property
of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Optically Clear Gloss Polyester (PET)
Adhesive	Optically Clear Removable Solvent-Acrylic Adhesive
Release Liner	Clear Polyester (PET)

PRODUCT CHARACTERISTICS

Film Thickness	4.6 mil (115µ)
Adhesive Layer	0.8 mil (20µ)
Outdoor Durability	2 Years (Unprinted)
Application Temperature	>23°F (-5°C)
Service Temperature Range	-40°F to 212°F (-40°C to 100°C)
Shelf Life	2 Years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity



Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013